



Mechanical and electrical specifications are subject to change without notice. Please contact us for precise details.

Les spécifications électriques et mécaniques peuvent changer sans pre-avis. Merci de nous contacter pour plus de précision.

KEY FEATURES

- 6-Side all-around fully IP-65 robust industrial-military Panel PC
- 15" Robust Industrial / Military-grade fully IP-65 Panel PC, Touch,
- Intel 100% fanless ULV duo 1.6GHz processor,
- Optional : boot up at -40 degree C
- Industrial and military grade high-end mainboard, Support 24h / 7 / 365 continuous running



Industrial Panel PC 15" PPC-15RT6-IP65

Specifications	
<p>Processor / Chipset Intel ULV duo 1.6GHz processor, Intel 945GSE and ICH7M chipsets GMA950 3D graphics engine, Support ActiveX 9.0 and OpenGL 3.0 Support 128MB high speed video share memory</p> <p>LCD Panel : 15" TFT LCD, 1024 x 768 resolution, 350 cd/m2 16.2 million true colors, 50,000 hours backlight 5-Wire resistive touch screen,</p> <p>RAM : DDR-II 1GB. (Optional : 2GB) HDD : SATA-II 160GB anti-shock anti-vibration slim</p> <p>LAN : IP-65 LAN port. Built-in dual Gigabit Ethernet 10 / 100 / 1000 Mbps networking (for IP65 rating, 1 x Giga bit LAN out) Option : Dual IP-65 Gb LAN</p> <p>I/Os - COM : IP-65 COM port. Total 6 Serial ports. (for IP-65 rating, 2x COM ports out) Option : 3, 4, 5, 6 COMs available</p> <p>- USB : IP-65 USB port. Total 8 USB 2.0 ports. (for IP-65 rating, 2x USB) Option : 4, 5, 6, 8 USBs available</p> <p>- PS2 : IP-65 PS2 port. Support PS2 keyboard and PS2 mouse</p> <p>- DIO : Optional 8 Digital Input and output ports</p> <p>- DVI : Optional DVI port .</p> <p>- VGA : IP65 VGA port supporting second monitor and Dual independent display with two different images</p> <p>- CF Slot : support 1G to 16G compact flash disk</p>	<p>O.S. Support Windows XP Pro-Embedded, Windows 7 Linux Ubuntu</p> <p>Watchdog Timer Support programmable watchdog timer from 1 ~ 255 seconds selectable from BIOS</p> <p>Mechanical - Robust rugged steel construction, support six sides all around fully IP-65, NEMA-4 water and dust resistant ratings. - Support VESA-75 wall-mounting. - 100% Fanless design</p> <p>Temperature Operating -10°C to +50 degree C Option : boot up at -40 degree C (patented heater module)</p> <p>Environmental Test standard - Vibration : meet industrial and military standards MIL-STD-810F - Shock : meet industrial and military standards MIL-STD-810F - EMI / EMC : meet industrial and MIL-STD-461E - Meet CE, FCC, RoHS, ETL standards.</p> <p>IP-65 Rating : 6 sides IP-65 / NEMA-4 water-resistant enclosure including all connectors.</p> <p>Power Consumption : around 50 watts</p> <p>Power Adapter : Standard : AC90-264V input Option : DC12V, 24V, 28V, 36V inputs</p>

Full range of all around IP-65 panel PC in multiple sizes

- PPC-7RT6-IP : 7" All around IP-65 Panel PC
- PPC-8RT6-IP : 8" All around IP-65 Panel PC
- PPC-10RT6-IP : 10", All around IP-65 Panel PC
- PPC-12RT6-IP : 12" All around IP-65 Panel PC
- PPC-15RT6-IP : 15" All around IP-65 Panel PC
- PPC-17RT6-IP : 17" All around IP-65 Panel PC
- PPC-19RT6-IP : 19", All around IP-65 Panel PC
- PPC-20RT6-IP : 20" All around IP-65 Panel PC
- PPC-22RT6-IP : 22" All around IP-65 Panel PC,
- PPC-32IT6-IP : 32" All around IP-65 Panel PC, (Infra-Red Touch)
- PPC-42IT6-IP : 42" All around IP-65 Panel PC, (Infra-Red Touch)